



- TEXTURED PORCELAIN TILES
- UNPOLISHED PORCELAIN TILES
- LAPPATO PORCELAIN TILES



PICTURES: by courtesy of Ceramiche Atlas Concorde S.p.a.

WHAT IT'S FOR

- Makes cleaning quick and easy and surfaces hygienic
- Improves the material's resistance to dirt
- Maintains the original appearance of the material over time

ADVANTAGES

- Provides prolonged protection over time
- For interior and exterior use
- High coverage
- Does not alter the material's anti-slip rating (tests conducted in conformity with **B.C.R.A.** and **ASTMC 1028-2007** methods).
- Does not form surface film
- UV resistant and non-yellowing

HOW TO USE IT

No dilution required: The product is ready to use.

Application instructions

Application for new installations:

1. Wash the floor thoroughly using **DETERDEK** (cement grout) or **FILACR10** (epoxy grout).
2. Apply **FILASTOP DIRT** to a clean and dry floor also treating the grout, covering evenly with a fleece or other suitable applicator.

Advice from the expert:

Given the product's high coverage, apply a moderate quantity of product to treat 2-3 m² of surface area at a time.

3. Rub the surface with a cloth or floor scrubber with white disc.
4. Fully remove any residues within 10 minutes, either manually using a microfibre cloth or with a single-disc floor scrubber.
5. After at least 12 hours, before treading on the treated surface, remove any product residues using a clean microfibre cloth.

Application on untreated surface to be restored:

1. Wash the floor using **FILAPS87** and/or **DETERDEK**.
2. Apply **FILASTOP DIRT** on the dry surface in the manner described above.

Caution:

The product may enhance the colour of the material or grouting; carry out a spot test beforehand. Aerate rooms during use. Do not apply to matt-finish lappato porcelain tiles.

COVERAGE

With one litre:

Textured, natural and Lappato porcelain tiles up to 70 m²

Coverage is indicative of one coat and may vary according to the material.

Packaging

500ml cans: 12-piece cartons.

COMPOSITION

A mixture of silicone resins dispersed in deaeromatised hydrocarbon solvent.

WARNINGS

This is a solvent-based product, the room should be aerated during application. Keep out of reach of children. Do not disperse into the environment after use. The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.

TEMPERATURES

Storage temperature: from 0°C to 30°C
The product should be applied to materials with temperature between 5° and 30°C.

LABELLING

Warning: Danger

Hazard indication:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

Caution recommendations: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Wear protective gloves / eye protection / face protection. IF SWALLOWED: immediately call a POISON CENTER / doctor. Dispose of contents / container in accordance with local/regional/national/international regulation. Contains: De-aromatized



mineral turpentine.

TECHNICAL FEATURES

Appearance: liquid

Colour: colourless

Odour: typical of hydrocarbon solvent

Density: 0.851 kg/l

Flammability: > 40° C

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring.

Fila shall not accept any responsibility for improper use of its products.